

TESLA TT34TP21-1232IAWUV



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI, UVC Sterilization.

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3400 (1000~3770) 3430 (1000~3810)	
Power input		W	1115 922	
Current input		A	5.80 4.70	
SEER-SCOP/ Energy Class		W/W	6,1/ A++ 4,0/A+	
Operating range		(°C)	-15°C - 53°C -20°C - 30°C	
Energy consumption (per year, based on standard test results)		kwh	195 840	
Dehumidifying		Kg/h	1.2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/II	
Max. input consumption		W	1720	
Max. current		A	10	
Compressor		Model	KSN98D32UEZ	
		Type	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	1170030067G	
		Power input	W 20W output	
		Capacity	uF 2	
		Indoor Fan Speed RPM	r/min ≤1320	
	Indoor fan	Dia. / Length	mm φ92×578	
	Indoor Air Circulation		m³/h	560
	Indoor Noise Level dB		dB(A)	22/25/33/37/41/50
	Net Dimension (L×W×H)		mm	790×275×192
	Packing Dimension (L×W×H)		mm	860×345×265
	Net Weight/Gross Weight		Kg	8/9,8
Outdoor	Fan motor	Model	1170040162AB	
		Power input	W 33W output	
		Capacity	uF /	
		Outdoor Fan Speed RPM	r/min ≤1000	
	Outdoor fan	Length	mm φ384×134	
	Outdoor Noise Level dB		dB(A)	29/33/39/46/50/60
	Net Dimension (L×W×H)		mm	777×290×495
	Packing Dimension (L×W×H)		mm	838×338×540
	Net Weight/Gross Weight		Kg	23,3/25,2
	Refrigerant type/weight		g	R32/550g
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
Refrigerant piping	Liquid side / Gas side		mm	6.35/9.52
	Max. refrigerant pipe length / Max. difference in level		m	25/10