

TESLA TT68TP21-2432IAWUV



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI, UVC Sterilization.



Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	6840 (1830~7820) 7050(1850~7960)	
Power input		W	2118 1900	
Current input		A	9.80 8.60	
SEER-SCOP/ Energy Class		W/W	6,5/ A++ 4,0/A+	
Operating range		(°C)	-15°C - 53°C -20°C - 30°C	
Energy consumption (per year, based on standard test results)		kwh	366 1537	
Dehumidifying		Kg/h	2.4	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2900	
Max. current		A	13.5	
Compressor		Model	C-6RZ146H3BAF	
		Type	Rotary	
		Brand	SANYO	
Indoor	Fan motor	Model	GGSDJ-23A	
		Power input	W	45W output
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	≤1280
	Indoor fan	Dia. / Length	mm	φ111.5X1010
	Indoor Air Circulation		m³/h	1100/1150
	Indoor Noise Level dB		dB(A)	31/34/38/42/47/58
	Net Dimension (LxWxH)		mm	1100×333×222
	Packing Dimension (LxWxH)		mm	1165×405×295
	Net Weight/Gross Weight		Kg	14/16
Outdoor	Fan motor	Model	GZSDJ-31(DC)	
		Power input	W	70W output
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	≤1000
	Outdoor fan	Length	mm	φ536×153
	Outdoor Noise Level dB		dB(A)	47/51/55/58/68
	Net Dimension (LxWxH)		mm	920×699×380
	Packing Dimension (LxWxH)		mm	960×732×400
	Net Weight/Gross Weight		Kg	40/43
	Refrigerant type/weight		g	R32/1140g
Max. Discharge/Max. Suction pressure		Mpa	3,7/1,2	
Refrigerant piping	Liquid side / Gas side		mm	6.35/15.88
	Max. refrigerant pipe length / Max. difference in level		m	25/10